www.marigold-industrial.com • www.marigold-industrial.com • www.marigold-industrial.com • www.marigold-industrial.com • www.marigold-industrial.com

G02T (formerly 2J/450)

DESCRIPTION

- Industrial protective glove.
- Natural rubber unsupported glove.
- 4 sizes available : 6½, 7½, 8½ and 9½.
- Trade unit : 12 pairs, 144 pairs in a transit case.

CHARACTERISTICS

- Natural rubber latex unsupported glove, flock lined 100% cotton for a better comfort.
- Long cuff for extra protection.
- Beaded cuff for tear resistance and easy donning.
- Length : 13" approx.
- Double wall thickness: 27 mil approx.

PERFORMANCES

- High resistance to water based chemicals.
- Roughened finish for excellent grip in damp conditions.
- Resistant and flexible, very comfortable.
- Tough general purpose natural rubber latex glove.
- In compliance with the standards EN420 (General requirements), EN388 (Mechanical Hazards) and EN374 (Chemical and Micro-organisms Hazards) by the notified laboratory BSI.
- Manufactured under EC quality assurance system carried out by the BSI.

APPLICATIONS

- CE Complex design.
- Applications : Ideal for laboratories and a broad range of chemical applications.

This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests, and manufactured under a CE quality assurance system carried out by a notified body.

CE 0086

EN420

2010

EN 388
Mechanical hazards

EN 388
- 2 Abrasion
- 0 Cut
- 1 Tear
- 0 Puncture

EN 420
- 5 Dexterity

AKL

EN 374
Chemical hazards

EN 374
- 3 A - Methanol
- 6 K - Caustic soda solution 40 %
- 3 L - Sulfuric acid 96 %

EN 374
Micro-organism hazards

Order codes

Sizes	6½ (S)	7½ (M)	8½ (L)	9½ (XL)
Orange Supaweight G02T	06431	06432	06433	06434